

**PAT-NO:** JP02003077560A  
**DOCUMENT-IDENTIFIER:** JP 2003077560 A

**TITLE:** ANISOTROPIC CONDUCTIVE SHEET AND MANUFACTURING METHOD THEREFOR

**PUBN-DATE:** March 14, 2003

**INVENTOR-INFORMATION:**

NAME	COUNTRY
YASUDA, TADASHI	N/A
SHIMODA, SUGIRO	N/A
KIMURA, KIYOSHI	N/A

For 10/586,768

**ASSIGNEE-INFORMATION:**

NAME	COUNTRY
JSR CORP	N/A

**APPL-NO:** JP2001262551  
**APPL-DATE:** August 31, 2001

**INT-CL (IPC):** H01R011/01 , H01B005/16 , H01B013/00

**ABSTRACT:**

**PROBLEM TO BE SOLVED:** To provide an anisotropic conductive sheet capable of preventing or suppressing adhesion of the sheet to a connected body, even if the sheet is used for a long period in a state of the sheet pressurized to the connected body under a high temperature environment, and manufacturing method therefor.

**SOLUTION:** This anisotropic conductive sheet is characterized by having 0.5 to 15  $\mu$ m surface roughness on at least one surface in the anisotropic conductive sheet showing conductivity in a thickness direction. This manufacturing method has a process for forming a forming material layer made by containing conductive particles showing magnetism between one surface side forming member and the

other surface side forming member in a material for a high molecular substance to be an elastic high molecular substance by being cured, applying a magnetic field to the forming material layer in the thickness direction and performing hardening treatment for the forming material layer. Surface roughening treatment is performed for a forming surface in contact with the forming material layer in at least the one surface side forming member.

COPYRIGHT: (C)2003,JPO